

BATERII SEMITRACTIUNE

GAMA TAB Motion GEL



Aplicatii Caravane, case mobile, masini de curatat industriale, carucioare electrice, UPS-uri, vehicule electrice usoare.

Caracteristici Baterii cu valva reguloatoare VRLA, placi plane si electrolit dizolvat in **GEL**. Fara intretinere. Complet sigilate. Pot fi folosite in industria farmaceutica si alimentara. Autodescargare redusa sub 2% / luna. 700 de cicluri la DoD 80% (IEC / EN 60254-1 / 25°C)

Tip Acumulator	Tens. (V)	C100 (Ah)	C20 (Ah)	C5 (Ah)	Dimensiuni (Lmm) x W(mm) x H(mm)	Gabarit EN 6095	Tip Fixare
50 GEL	12V	70	60	50	278 x 175 x 190	L3	B13
70 GEL	12V	90	80	70	353 x 175 x 190	L5	B13
75 GEL	12V	130	85	75	352 x 175 x 211 x 232	60528	B1
105 GEL	12V	140	125	105	345 x 173 x 264 x 285	62512	B0
130 GEL	12V	165	150	130	514 x 223 x 195 x 222	B	B0
180 GEL	12V	235	210	180	518 x 273 x 214 x 240	C	B0
180 Golf Cart GEL	6V	235	210	180	243 x 189 x 252 x 273	Golf Cart GEL	B0



GAMA TAB Motion AGM



Aplicatii Rulate de vacanta, barci, scaune electrice, masini de curatat industriale sisteme de alarma, UPS-uri.

Caracteristici Baterii cu valve VRLA si separatori AGM. Fiabilitate si rezistenta la vibratii excelente. Fara intretinere. 400 de cicluri la DoD 80% (IEC / EN 60254-1 / 25°C). Complet sigilate si fara scurgeri. Pot fi folosite in industria alimentara si farmaceutica.

Tip Acumulator	Tens. (V)	C100 (Ah)	C20 (Ah)	C5 (Ah)	Dimensiuni (Lmm) x W(mm) x H(mm)	Gabarit EN 6095	Tip Fixare
45 AGM	12V	65	60	45	242 x 175 x 190	L2	B13
55 AGM	12V	75	70	55	278 x 175 x 190	L3	B13
60 AGM	12V	85	80	60	315 x 175 x 190	L4	B13
70 AGM	12V	115	105	80	353 x 175 x 190	L5	B13

