

## GENERAL FEATURES

- Environmentally friendly
- Can be used at vertical or horizontal orientation
- High Reliability and Good Quality
- High gas recombination efficiency
- High Power Density
- Maintenance-Free Operation


## APPLICATIONS

- UPS & EPS
- Emergency lighting Systems
- Medical Equipment
- Cable TV Systems
- Alarm Systems
- Electric Test Equipment
- Security Systems



## DIMENSIONS & WEIGHT

Length(mm)	229±1
Width(mm)	138±1
Height(mm)	208±1
Total Height(mm)	212±1
Weight(kg)	17.3±3%



## COMPLIED STANDARDS

IEC 60896-21/22	JIS C8704
YD/T799	BS6290 part4
GB/T 19638	UL 1989

## TECHNICAL SPECIFICATIONS



Nominal Voltage		12V(6 cells per unit)
Design Floating Life @25°C		10 Years
Nominal Capacity @25°C(10 hour rate@5.80A,10.80V)		58Ah
Capacity @25°C	20 hour rate (3.10A,10.5V)	62.0Ah
	5 hour rate (10.2A,10.5V)	51.0Ah
	1 hour rate (37.0A,9.6V)	37.0Ah
Internal Resistance	Full Charged Battery@25°C	≤7.2mΩ
Ambient Temperature	Discharge	-20°C~50°C
	Charge	-20°C~50°C
	Storage	-20°C~50°C
Max.Discharge Current@25°C		580A(5s)
Capacity affected by Temperature (10 hr Capacity )	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-Discharge@25°C per Month		3%
Charge (Constant Voltage) @25°C	Standby Use	Initial Charging Current Less than 14.5A Voltage 13.6-13.8V
	Cycle Use	Initial Charging Current Less than 14.5A Voltage 14.4-14.9V

## BATTERY DISCHARGE TABEL

### Discharge Constant Current per Cell (Amperes at 25°C)







F.V/Time	15min	30min	45min	1h	2h	3h	5h	6h	8h	10h	20h
1.60V	104.7	61.7	46.7	37.0	21.8	16.0	10.8	9.4	7.4	6.1	3.22
1.67V	98.9	58.4	44.9	35.9	21.1	15.5	10.6	9.2	7.3	6.0	3.19
1.70V	92.9	56.7	43.3	34.5	20.5	15.1	10.4	9.0	7.2	5.9	3.14
1.75V	87.0	54.2	41.4	33.1	20.0	14.7	10.2	8.9	7.1	5.9	3.10
1.80V	81.6	52.3	39.8	32.0	19.2	14.3	10.0	8.7	7.0	5.8	3.07

### Discharge Constant Power per Cell (Watts at 25°C)

F.V/Time	15min	30min	45min	1h	2h	3h	5h	6h	8h	10h	20h
1.60V	200.2	122.4	88.7	71.0	41.2	30.6	20.8	18.2	14.4	11.9	6.4
1.67V	191.5	114.8	85.7	69.1	40.1	29.8	20.5	17.9	14.3	11.8	6.3
1.70V	178.5	112.3	82.9	66.7	39.2	29.1	20.2	17.6	14.1	11.7	6.2
1.75V	167.4	106.9	79.6	64.3	38.3	28.5	19.9	17.3	13.9	11.5	6.2
1.80V	157.2	102.5	77.0	62.2	37.0	27.7	19.5	17.1	13.7	11.5	6.1

**Note** The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values. Cell and battery designs/specifications are subject to modification without notice. Contact MCA for the latest information.

## PERFORMANCE CHARACTERISTICS



## BATTERY CONSTRUCTION

Component	Positive plate	Negative plate	Container & Cover	Safety valve	Terminal	Separator	Electrolyte	Pillar seal
Features	Thick high Sn low Ca grid with special paste	Balanced Pb-Ca grid for improved recombination efficiency	ABS (UL94-V0 optional)	Flame Si-Rubbeand aging resistancer	Female Copper Insert M6(torque:4~6N.m)	Advanced AGM separator for high pressure cell design	Dilute high purity sulphuric acid	Two layers epoxy resin seal